

INTEGRATIVE TECHNICAL DATA SHEET FOR SUNFLOWER HEADER

MODEL		500 N	550 N	600 N	670 N	740 N	940 N	1200 N
dimensions	Height, m	1,1	1,1	1,1	1,1	1,1	1,1	1,1
	Max. width, m	5,2	5,7	6,2	6,9	7,6	9,4	12,10
	Cutting width, m	5	5,5	6	6,7	7,4	9,2	11,90
	Depth, m	2,35	2,35	2,35	2,35	2,35	2,35	2,35
	Weight, kg	1.650	1.800	1.900	2.000	2.200	2.700	3.200
PTO absorbed power		35/40 Hp	35/40 Hp	35/40 Hp	35/40 Hp	35/40 Hp	35/40 Hp	35/40 Hp (sx + dx)
PTO revolutions (approx.)		570	570	570	570	570	570	570
Conveyor roller (diameter, mm)		240	240	240	240	240	300	300
Spiral Conveyor roller (diameter, mm)		540x500x240	540x500x240	540x500x240	540x500x240	540x500x240	540x500x300	540x500x300
Conveyor roller drive		mechanical	mechanical	mechanical	mechanical	mechanical	mechanical	mechanical
Conveyor roller revolutions (approx.), rpm.		170	170	170	170	170	170	170
Oscillating transmission box revolutions, rpm		346	346	346	346	346	346	346
Transmission box oil (type)		85W140	85W140	85W140	85W140	85W140	85W140	85W140
Cutting blade strokes (strokes/min)		692	692	692	692	692	692	692
Compactor reel		1	1	1	1	1	1	1
Compactor reel revolutions (approx.)		45	45	45	45	45	45	45
Mounting (type)		central	central	central	central	central	off-center to the left	central
Numero di punte		20	22	24	27	30	38	50